

PRESS MASTERS

Solutions for the Metalforming Industry

Minster E2-400-96 Hevi-Stamper Double Eccentric Straight Side Press

Stock #300014P

New 1978



Photo of similar press

Press Specifications:

Tonnage, heavy duty rating:400 Tons
Stroke of Slide: 12.00 “
Adjustment of Slide:6.00 “
Shutheight SDAU:22.00”, on Bolster
Shutheight SDAU:29.00”, on Bed
Bolster Plate Thickness:7.00 “
Area of Slide, R-L x F-B:96.00 x 48.00”
Area of Bed, R-L x F-B:96.00 x 48.00”
Area of Bolster, R-L x F-B:96.00 x 48.00”
Opening in Bed, R-L x F-B, w/1 rib:90.00 x 30.00 “
Distance between Gib surfaces, R-L:98.00”
Floor to top of Bed (floor mounted):38.00”
Upright Opening, F-B:31.00”
Speed:0-80 SPM
Drive Motor Power, RPM:75HP, 1800 RPM
Approximate Press Weight:140,000 pounds

Equipped With:

Single geared
Twin driving gears on main shaft, extensions both ends
Minster combination air operated clutch and brake
Minster Centralized Motor and Clutch Control
Air operated flywheel brake, electrically interlocked
Pneumatic counter balance
Motorized slide adjustment with direct reading shutheight indicator
Minster “Monitorflow” lubrication system
Arranged for 3 crossbar knockout
Slide Face machined with standard T-slots
Bolster plate machined with standard T-slots
Eddy Current Drive Motor

Price, As Is Where Is:Contact Press Masters

Note: All specifications contained herein are as the machine was originally manufactured and are subject to change at time of inspection.

Corporate Office

55 Realty Drive, Suite 100 • Cheshire, CT 06410
(203) 271-0644 • (203) 439-9116 Fax
www.pressmasters.com

Request Quote