

# PRESS MASTERS

**Solutions for the Metalforming Industry**

## Refurbished P2-100-48 Straight Side Press

New 1997

Stock #100142P



Photo of similar press

### Press Specifications:

Tonnage, heavy duty rating: .....100 Tons  
Stroke of Slide: .....1.50 in.  
Adjustment of Slide: .....2.00 in.  
Shutheight SDAU: .....15.00in., on Bolster  
Shutheight SDAU: .....20.00in., on Bed  
Bolster Plate Thickness: .....5.00 in.  
Area of Slide, R-L x F-B: .....48.00 x 18.5.00 in.  
Area of Bed, R-L x F-B: .....48.00 x 31.00 in.  
Area of Bolster, R-L x F-B: .....48.00 x 31.00 in.  
Opening in Bed, R-L x F-B: .....41.00 x 15.00 in.  
Distance between Gib surfaces, R-L: .....50.00 in.  
Floor to top of Bed: .....36.00 in.  
Upright Opening, F-B: .....16.00 in.  
Speed: .....0-450 SPM  
Drive Motor Power, RPM: .....20HP, 1800 RPM  
Approximate Press Weight: .....27,600 pounds

### Equipped With:

Flywheel type with belt drive  
RH drive, extension on opposite end  
Minster combination air operated clutch and brake  
Air operated flywheel brake, electrically interlocked  
Pneumatic counter balance  
Arranged for detachable air slide adjusting device  
with 5 digit shutheight indicator  
Minster "Monitorflow" lubrication system  
Minster Centralized Motor and Clutch Control  
Pedestal Style Main Control Enclosure w/Standpipe  
Eddy Current Drive Motor  
Power off Manual Bumping Arrangement  
A-3 Acoustical Die Space Enclosures, interlocked  
Wintriss SmartPAC operator interface

- 16 Channel ProCamPAC
- 8 Channel DieProPAC
- Brake Monitor

**Price:** .....**Contact Press Masters**

Note: All specifications contained herein are as the machine was originally manufactured and are subject to change at time of inspection.

### **Corporate Office**

55 Realty Drive, Suite 100 • Cheshire, CT 06410  
(203) 271-0644 • (203) 439-9116 Fax  
[www.pressmasters.com](http://www.pressmasters.com)

**Request Quote**